



CP100DMOY

Print Horizontal Double Way (Arrow) Sign Marked

Product Control Unit

Model Spring

Type Flush

Contact 1NO

Color Blue

Dia 22 mm

Current **Ie** 4 A (230V AC)

Usage Category AC 15

Mechanical Life **Min Qty** 500000

Electrical Life **Min Qty** 100000

Operating Frequency **On-Off/Hour** Mech. 3000 Elec. 1200

Insulation Voltage **Ui** 300V

Impulse Withstand Voltage **Uimp** 2.5 kV

Dielectric Strength (Body-Contact) 2.500V AC

Dielectric Strength (Contact-Contact) 1.500V AC

Isolation Resistance 10 MΩ min. (500V DC)

Operating Temperature -15 / + 65 °C

Pollution Degree 3

Protection Degree IP65

Contact Material AgNi

Cable Section 1.5-2.5 mm²

Screw Torque 1,5 Nm

Short Circuit Breaking Capacity **Ics** 1 kA

Production Time 31.12.1899 00:00:00

Serial CP Series Plastic

Specifications Non-flammable V0 PA6.6 contact blocks

Various illumination contact blocks availability

Variety of products for all areas of application

IP65 protection from front side

Standards / Certificates IEC 60947-5-1 TS EN 60947-5-1 UL 508 VDE 0660

