

**IF5M024XRM05**

|                              |  |                            |
|------------------------------|--|----------------------------|
| <b>Operational Frequency</b> |  | 50 Hz                      |
| <b>Operational Voltage</b>   |  | 24V AC/DC                  |
| <b>Product</b>               |  | LED Beacon 55mm            |
| <b>Control</b>               |  | Key Control                |
| <b>Mounting</b>              |  | M22 Screw                  |
| <b>Color</b>                 |  | Multicolor                 |
| <b>Illumination</b>          |  | Rotational                 |
| <b>Insulation Voltage</b>    | <b>Ui</b>  | 300V                       |
| <b>Operating Temperature</b> |  | -25 °C /+70 °C             |
| <b>Protection Degree</b>     |  | IP65                       |
| <b>Cable Section</b>         |  | Cable 0,50 mm <sup>2</sup> |
| <b>Production Time</b>       |  | 31.12.1899 00:00:00        |
| <b>Serial</b>                |  | IF Series                  |
| <b>Electrical Life</b>       | <b>Min Hour</b>  | 10000                      |
| <b>Specifications</b>        | Heat resistant, clear vision Polycarbonate signal module |                            |
|                              | Monoblock construction                                   |                            |
|                              | Easy wiring  |                            |
|                              | Easy to install to 22mm hole                             |                            |

