

**IF6P024ZM05-5**

<b>Operational Frequency</b>		50 Hz
<b>Operational Voltage</b>		24V DC
<b>Product</b>		LED Beacon 65mm
<b>Control</b>		PLC Harmonized
<b>Mounting</b>		M22 Screw
<b>Color</b>		Multicolor
<b>Illumination</b>		Constant
<b>Cable</b>		5mt Cable
<b>Volume</b>		90 - 105 dB
<b>Power Consumption (Red)</b>		1.1W
<b>Power Consumption (Yellow)</b>		1.4W
<b>Power Consumption (Blue)</b>		1.1W
<b>Power Consumption (Green)</b>		1.2W
<b>Power Consumption (White)</b>		2.7W
<b>Power Consumption (Buzzer - Low Level)</b>		0.75W
<b>Power Consumption (Buzzer - High Level)</b>		1.25W
<b>Operating Frequency</b>	<b>On-Off/Hour</b>	1 Hz
<b>Insulation Voltage</b>	<b>Ui</b>	300V
<b>Operating Temperature</b>		-25 °C /+70 °C
<b>Protection Degree</b>		IP65
<b>Cable Section</b>		Cable 0,50 mm <sup>2</sup>
<b>Production Time</b>		31.12.1899 00:00:00
<b>Serial</b>		IF Series
<b>Buzzer</b>		With Buzzer
<b>Electrical Life</b>	<b>Min Hour</b>	10000

**Specifications**

Heat resistant, clear vision Polycarbonate signal module

Monoblock construction

Easy wiring

Easy to install to 22mm hole

