

**IK72F024ZM01**

<b>Weight (Gross with Carton)</b>	<b>Gr</b>	354
<b>Bulb Type</b>		LED
<b>Operational Frequency</b>		50 Hz
<b>Operational Voltage</b>		24V AC/DC
<b>Product</b>		LED Tower 70mm
<b>Mounting</b>		110mm Plastic Tube and Base
<b>Color</b>		Three Level
<b>Illumination</b>		Flasher
<b>Volume</b>		90 dB
<b>Power Consumption</b>		3W
<b>Operating Frequency</b>	<b>On-Off/Hour</b>	1 Hz
<b>Insulation Voltage</b>	<b>Ui</b>	300V
<b>Operating Temperature</b>		-25 °C /+70 °C
<b>Protection Degree</b>		IP40
<b>Cable Section</b>		0,75-1,5 mm <sup>2</sup>
<b>Screw Torque</b>		1,8Nm
<b>Lampholder Type</b>		BA15S
<b>Production Time</b>		31.12.1899 00:00:00
<b>Serial</b>		IK Series
<b>Buzzer</b>		With Buzzer
<b>Electrical Life</b>	<b>Min Hour</b>	10000
<b>Specifications</b>		Heat resistant, clear vision Polycarbonate signal modules
		Modular construction
		Easy wiring
		Variety of connection bases

