

**IK73L024XM01E**

|                                   |                 |   |
|-----------------------------------|-----------------|---|
| <b>Weight (Gross with Carton)</b> | <b>Gr</b>       | 343   |
| <b>Bulb Type</b>                  |                 | LED   |
| <b>Operational Frequency</b>      |                 | 50 Hz   |
| <b>Operational Voltage</b>        |                 | 24V AC/DC   |
| <b>Product</b>                    |                 | LED Tower 70mm  |
| <b>Mounting</b>                   |                 | 110mm Plastic Tube and Base with Etange                   |
| <b>Color</b>                      |                 | Three Level   |
| <b>Power Consumption</b>          |                 | 3W  |
| <b>Insulation Voltage</b>         | <b>Ui</b>       | 300V  |
| <b>Operating Temperature</b>      |                 | -25 °C /+70 °C  |
| <b>Protection Degree</b>          |                 | IP65  |
| <b>Cable Section</b>              |                 | 0,75-1,5 mm <sup>2</sup>                                  |
| <b>Screw Torque</b>               |                 | 1,8Nm   |
| <b>Lampholder Type</b>            |                 | BA15S   |
| <b>Production Time</b>            |                 | 31.12.1899 00:00:00                                       |
| <b>Serial</b>                     |                 | IK Series   |
| <b>Electrical Life</b>            | <b>Min Hour</b> | 10000   |
| <b>Specifications</b>             |                 | Heat resistant, clear vision Polycarbonate signal modules |
|                                   |                 | Modular construction                                      |
|                                   |                 | Easy wiring   |
|                                   |                 | Variety of connection bases                               |

