




| MBSD012S              |                                       |                         |
|-----------------------|---------------------------------------|-------------------------|
| Bulb Type             |                                       | Led                     |
| Operating Current     |                                       | 18 mA                   |
| Operational Frequency |                                       | 50 Hz                   |
| Operational Voltage   |                                       | 12V AC/DC               |
| Product               |                                       | Pilot                   |
| Color                 |                                       | Yellow                  |
| Illumination          |                                       | with LED                |
| Dia                   |                                       | 22 mm                   |
| Power Consumption     |                                       | 0.3 W                   |
| Insulation Voltage    | Ui                                    | 250 V                   |
| Operating Temperature |                                       | -15 / + 70 °C           |
| Protection Degree     |                                       | IP50                    |
| Cable Section         |                                       | 1.5-2.5 mm <sup>2</sup> |
| Screw Torque          |                                       | 1,5 Nm                  |
| Production Time       |                                       | 31.12.1899 00:00:00     |
| Serial                |                                       | MB Series Plastic       |
| Electrical Life       | Min Hour                              | 10000                   |
| Specifications        | Non-flammable V0 PA6.6 contact blocks |                         |
|                       | Monoblock strong bod                  | У                       |
|                       | Finger safe protection                |                         |
|                       |                                       |                         |











Montaj Ölçüsü Ø22.4  $\pm 0.2 \text{ mm}$ 

