



### MKS1TM-0.40

Operational Frequency		50-60 Hz
Product		Motor Protection Switch
Current	<b>I<sub>e</sub></b>	25 A
Thermic Current Calibration Interval		0,25-0,40A
Usage Category		AC 3
Mechanical Life	<b>Min Qty</b>	100000
Electrical Life	<b>Min Qty</b>	100000
Operating Frequency	<b>On-Off/Hour</b>	Mek. 360 Elk. 360
Insulation Voltage	<b>U<sub>i</sub></b>	690V AC
Impulse Withstand Voltage	<b>U<sub>imp</sub></b>	6 kV
Dielectric Strength (Contact-Contact)		1890V
Isolation Resistance		10 MΩ Min. (500 V DC)
Operating Temperature		-5 / +40 °C
Pollution Degree		3
Protection Degree		IP40
Cable Section		0,75-4 mm <sup>2</sup>
Screw Torque		1,8 Nm
Short Circuit Breaking Capacity	<b>I<sub>cs</sub></b>	6 kA
Production Time		Adjustable overload release 13 ranges between 0.1-25 A; Short circuit release factor set at 12xI <sub>e</sub> ; Short circuit switching capacity minimum 6 kA / 400 V
Serial Specifications		MKS Series Adjustable overload release 13 ranges between 0.1-25 A Short circuit release factor set at 12xI <sub>e</sub> Short circuit switching capacity minimum 6 kA / 400 V
Standards / Certificates		TS EN 60947-4-1

CE

ERT



TSE

UK  
PA