

PA1115

| | | |
|--|--------------------|--|
| Product | | Lift Station |
| Color | | Yellow-Black |
| Current | Ie | 4A (250V AC) |
| Usage Category | | AC15 |
| Mechanical Life | Min Qty | 1000000 |
| Electrical Life | Min Qty | 100000 |
| Operating Frequency | On-Off/Hour | Mech. 3000 Elec. 1200 |
| Insulation Voltage | Ui | 300 V |
| Impulse Withstand Voltage | Uimp | 2.5 kV |
| Dielectric Strength (Body-Contact) | | 2.500V AC |
| Dielectric Strength (Contact-Contact) | | 1.500V AC |
| Isolation Resistance | | 10 MΩ (500 V DC) |
| Operating Temperature | | -15 / + 80 °C |
| Pollution Degree | | 3 |
| Protection Degree | | IP65 |
| Contact Material | | AgNi |
| Cable Section | | 1.5-2.5 mm ² |
| Screw Torque | | 1.5Nm |
| Short Circuit Breaking Capacity | Ics | 1kA |
| Production Time | | Aug.22 |
| Serial | | PA Series |
| Hole Qty | | 1 Hole |
| Ingredients | | CP200EP |
| Specifications | | Suitable for Ø22 mm control units Aesthetic, durable and ergonomic design |
| Standards / Certificates | | TS EN 60947-5-1 UL 508 VDE 0660 |

