



PA4406		
Product		Lift Station
Feature		with Cable Gland
Color		Yellow-Black
Current	I_e	4A (250V AC)
Usage Category		AC15
Mechanical Life	Min Qty	1000000
Electrical Life	Min Qty	100000
Operating Frequency	On-Off/Hour	Mech. 3000 Elec. 1200
Insulation Voltage	U_i	300 V
Impulse Withstand Voltage	U_{imp}	2.5 kV
Dielectric Strength (Body-Contact)		2.500V AC
Dielectric Strength (Contact-Contact)		1.500V AC
Isolation Resistance		10 MΩ (500 V DC)
Operating Temperature		-15 / + 80 °C
Pollution Degree		3
Protection Degree		IP65
Contact Material		AgNi
Cable Section		1.5-2.5 mm ²
Screw Torque		1.5Nm
Short Circuit Breaking Capacity	I_{cs}	1kA
Serial		PA Series
Hole Qty		4 Holes
Ingredients		CP200EP + CP101DBOD + CP101DHOD + PSA020ZS332AR + CMUHAFZA
Specifications		Suitable for Ø22 mm control units Aesthetic, durable and ergonomic design
Standards / Certificates		TS EN 60947-5-1 UL 508 VDE 0660

CE

ERT

