



<b>PA8801</b>	
<b>Product</b>	Lift Station
<b>Color</b>	Yellow-Black
<b>Current</b>	<b>Ie</b> 4A (250V AC)
<b>Usage Category</b>	AC15
<b>Mechanical Life</b>	<b>Min Qty</b> 1000000
<b>Electrical Life</b>	<b>Min Qty</b> 100000
<b>Operating Frequency</b>	<b>On-Off/Hour</b> Mech. 3000 Elec. 1200
<b>Insulation Voltage</b>	<b>Ui</b> 300 V
<b>Impulse Withstand Voltage</b>	<b>Uimp</b> 2.5 kV
<b>Dielectric Strength (Body-Contact)</b>	2.500V AC
<b>Dielectric Strength (Contact-Contact)</b>	1.500V AC
<b>Isolation Resistance</b>	10 MΩ (500 V DC)
<b>Operating Temperature</b>	-15 / + 80 °C
<b>Pollution Degree</b>	3
<b>Protection Degree</b>	IP65
<b>Contact Material</b>	AgNi
<b>Cable Section</b>	1.5-2.5 mm <sup>2</sup>
<b>Screw Torque</b>	1.5Nm
<b>Short Circuit Breaking Capacity</b>	<b>Ics</b> 1kA
<b>Serial</b>	PA Series
<b>Hole Qty</b>	8 Holes
<b>Ingredients</b>	CP200E + CP101DBOD + CP101DHOD + CP101K20HSZL + CP100DMOO + CP101S30 + CP101S30 + PSA020KD340AR
<b>Specifications</b>	Suitable for Ø22 mm control units Aesthetic, durable and ergonomic design
<b>Standards / Certificates</b>	TS EN 60947-5-1 UL 508 VDE 0660

CE

ERL



PA8801

