



PARK4M2

| | | |
|---------------------------------------|------------------------------------------------------------------------------|-----------------------|
| Product | Lift Station | |
| Color | Yellow-Black | |
| Current | Ie | 4A (250V AC) |
| Usage Category | AC15 | |
| Mechanical Life | Min Qty | 1000000 |
| Electrical Life | Min Qty | 100000 |
| Operating Frequency | On-Off/Hour | Mech. 3000 Elec. 1200 |
| Insulation Voltage | Ui | 300 V |
| Impulse Withstand Voltage | Uimp | 2.5 kV |
| Dielectric Strength (Body-Contact) | 2.500V AC | |
| Dielectric Strength (Contact-Contact) | 1.500V AC | |
| Isolation Resistance | 10 MΩ (500 V DC) | |
| Operating Temperature | -15 / + 80 °C | |
| Pollution Degree | 3 | |
| Protection Degree | IP65 | |
| Contact Material | AgNi | |
| Cable Section | 1.5-2.5 mm ² | |
| Screw Torque | 1.5Nm | |
| Short Circuit Breaking Capacity | Ics | 1kA |
| Serial | PARK Series | |
| Hole Qty | 4 Holes | |
| Ingredients | CP101DBOD + CP200E + CP101DHOD + TIPASOM | |
| Specifications | Suitable for Ø22 mm control units Aesthetic, durable and ergonomic design | |
| Standards / Certificates | TS EN 60947-5-1 UL 508 VDE 0660 | |

PARK4M2

