



### PDKS11UX20

|                                       |                    |                          |
|---------------------------------------|--------------------|--------------------------|
| Carton Box pieces                     | <b>Qty</b>         | 1                        |
| Product                               |                    | Foot Switch              |
| Feature                               |                    | Single                   |
| Contact                               |                    | 3*(1NO+1NC) 1+2          |
| Color                                 |                    | Yellow                   |
| Protection                            |                    | Metal Protection         |
| Current                               | <b>Ie</b>          | 3 A (240V AC)            |
| Usage Category                        |                    | AC15                     |
| Mechanical Life                       | <b>Min Qty</b>     | 1000000                  |
| Electrical Life                       | <b>Min Qty</b>     | 100000                   |
| Operating Frequency                   | <b>On-Off/Hour</b> | Mech. 1800 Elec. 1200    |
| Insulation Voltage                    | <b>Ui</b>          | 300 V                    |
| Impulse Withstand Voltage             | <b>Uimp</b>        | 2.5 kV                   |
| Dielectric Strength (Body-Contact)    |                    | 2.500V AC                |
| Dielectric Strength (Contact-Contact) |                    | 1.500V AC                |
| Isolation Resistance                  |                    | 10 MΩ min. (500V DC)     |
| Operating Temperature                 |                    | -25 / +80 °C             |
| Pollution Degree                      |                    | 3                        |
| Protection Degree                     |                    | IP65                     |
| Contact Material                      |                    | AgNi                     |
| Cable Section                         |                    | 1.5-2.5 mm <sup>2</sup>  |
| Screw Torque                          |                    | 1.5Nm                    |
| Short Circuit Breaking Capacity       | <b>Ics</b>         | 1 kA                     |
| Body Material                         |                    | Plastic                  |
| Production Time                       |                    | 31.12.1899 00:00:00      |
| Serial                                |                    | PDK Series               |
| Step                                  |                    | Double Step              |
| Specifications                        |                    | Plastic or Metal options |

Single and Double Speed

Yellow

Grey and orange color options

with Latching option

**Standards / Certificates** TS EN 60947-5-1 UL 508 VDE 0660



PDKS11UX20

