



<b>PTM111</b>		
<b>Product</b>		Thermostat
<b>Feature</b>		Single
<b>Contact</b>		1NO
<b>Color</b>		Blue
<b>Current</b>	<b>Ie</b>	10 A (230V AC)
<b>Usage Category</b>		AC15
<b>Mechanical Life</b>	<b>Min Qty</b>	50000
<b>Electrical Life</b>	<b>Min Qty</b>	50000
<b>Operating Frequency</b>	<b>On-Off/Hour</b>	Mech. 900 Elec. 900
<b>Insulation Voltage</b>	<b>Ui</b>	300V
<b>Dielectric Strength (Body-Contact)</b>		1.000V AC
<b>Dielectric Strength (Contact-Contact)</b>		1.000V AC
<b>Isolation Resistance</b>		10 MΩ min. (500V DC)
<b>Operating Temperature</b>		-25 / +80 °C
<b>Pollution Degree</b>		3
<b>Protection Degree</b>		IP20
<b>Contact Material</b>		AgNi
<b>Cable Section</b>		1-2.5 mm <sup>2</sup>
<b>Screw Torque</b>		1,5 Nm
<b>Short Circuit Breaking Capacity</b>	<b>Ics</b>	1 kA
<b>Serial</b>		PTM Series
<b>Specifications</b>		Sensitive setting
		Plastic housing, DIN rail mountable
<b>Standards / Certificates</b>		TS EN 60730-2-9



