



PTM122

| | | |
|--|-------------------------------------|---------------------|
| Product | Thermostat | |
| Feature | Double | |
| Contact | 1NO+1NC | |
| Color | Red-Blue | |
| Current | I_e | 10 A (230V AC) |
| Usage Category | AC15 | |
| Mechanical Life | Min Qty | 50000 |
| Electrical Life | Min Qty | 50000 |
| Operating Frequency | On-Off/Hour | Mech. 900 Elec. 900 |
| Insulation Voltage | U_i | 300V |
| Dielectric Strength (Body-Contact) | 1.000V AC | |
| Dielectric Strength (Contact-Contact) | 1.000V AC | |
| Isolation Resistance | 10 MΩ min. (500V DC) | |
| Operating Temperature | -25 / +80 °C | |
| Pollution Degree | 3 | |
| Protection Degree | IP20 | |
| Contact Material | AgNi | |
| Cable Section | 1-2.5 mm ² | |
| Screw Torque | 1,5 Nm | |
| Short Circuit Breaking Capacity | I_{cs} | 1 kA |
| Serial | PTM Series | |
| Specifications | Sensitive setting | |
| | Plastic housing, DIN rail mountable | |
| Standards / Certificates | TS EN 60730-2-9 | |



