



### PV3AC20B4

Product		Crane Pendant Station
Type		3 Hole
Contact		1NC
Current	<b>I<sub>e</sub></b>	4A (250V AC)
Usage Category		AC15
Mechanical Life	<b>Min Qty</b>	1000000
Electrical Life	<b>Min Qty</b>	100000
Operating Frequency	<b>On-Off/Hour</b>	Mech. 900 Elec. 900
Insulation Voltage	<b>U<sub>i</sub></b>	300 V
Impulse Withstand Voltage	<b>U<sub>imp</sub></b>	2.5 kV
Dielectric Strength (Body-Contact)		2.500V AC
Dielectric Strength (Contact-Contact)		1.500V AC
Isolation Resistance		10 MΩ (500 V DC)
Operating Temperature		-15 / + 80 °C
Pollution Degree		3
Protection Degree		IP65
Contact Material		AgNi
Cable Section		1.5-2.5 mm <sup>2</sup>
Screw Torque		1.5Nm
Short Circuit Breaking Capacity	<b>I<sub>cs</sub></b>	1kA
Production Time		15.08.2022 00:00:00
Serial		PV Series
Speed		Double Speed
1.Hole		Key Selector
Specifications		Aesthetic look and ergonomic usage with assistance of ABS reinforced material
		Mechancial interlock
		Single and double speed

Standards / Certificates TS EN 60947-5-1 UL 508 VDE 0660

