



<b>PV3T1X</b>	
<b>Product</b>	Crane Pendant Station
<b>Type</b>	3 Hole
<b>Current</b>	<b>Ie</b> 4A (250V AC)
<b>Usage Category</b>	AC15
<b>Mechanical Life</b>	<b>Min Qty</b> 1000000
<b>Electrical Life</b>	<b>Min Qty</b> 100000
<b>Operating Frequency</b>	<b>On-Off/Hour</b> Mech. 900 Elec. 900
<b>Insulation Voltage</b>	<b>Ui</b> 300 V
<b>Impulse Withstand Voltage</b>	<b>Uimp</b> 2.5 kV
<b>Dielectric Strength (Body-Contact)</b>	2.500V AC
<b>Dielectric Strength (Contact-Contact)</b>	1.500V AC
<b>Isolation Resistance</b>	10 MΩ (500 V DC)
<b>Operating Temperature</b>	-15 / + 80 °C
<b>Pollution Degree</b>	3
<b>Protection Degree</b>	IP65
<b>Contact Material</b>	AgNi
<b>Cable Section</b>	1.5-2.5 mm <sup>2</sup>
<b>Screw Torque</b>	1.5Nm
<b>Short Circuit Breaking Capacity</b>	<b>Ics</b> 1kA
<b>Serial</b>	PV Series
<b>Speed</b>	Blank
<b>1.Hole</b>	Blind Cap
<b>Specifications</b>	Aesthetic look and ergonomic usage with assistance of ABS reinforced material
	Mechanical interlock
	Single and double speed
<b>Standards / Certificates</b>	TS EN 60947-5-1 UL 508 VDE 0660

CE

ERT



PV3T1X

