

**PV5AC20B44**

| | | |
|--|------------------------|---|
| Product | | Crane Pendant Station |
| Type | | 5 Hole |
| Contact | | 1NC |
| Current | I_e | 4A (250V AC) |
| Usage Category | | AC15 |
| Mechanical Life | Min Qty | 1000000 |
| Electrical Life | Min Qty | 100000 |
| Operating Frequency | On-Off/Hour | Mech. 900 Elec. 900 |
| Insulation Voltage | U_i | 300 V |
| Impulse Withstand Voltage | U_{imp} | 2.5 kV |
| Dielectric Strength (Body-Contact) | | 2.500V AC |
| Dielectric Strength (Contact-Contact) | | 1.500V AC |
| Isolation Resistance | | 10 MΩ (500 V DC) |
| Operating Temperature | | -15 / + 80 °C |
| Pollution Degree | | 3 |
| Protection Degree | | IP65 |
| Contact Material | | AgNi |
| Cable Section | | 1.5-2.5 mm ² |
| Screw Torque | | 1.5Nm |
| Short Circuit Breaking Capacity | I_{cs} | 1kA |
| Production Time | | 13.12.2021 00:00:00 |
| Serial | | PV Series |
| Speed | | Double Speed |
| 1.Hole | | Key Selector |
| Specifications | | Aesthetic look and ergonomic usage with assistance of ABS reinforced material |
| | | Mechancial interlock |
| | | Single and double speed |

Standards / Certificates TS EN 60947-5-1 UL 508 VDE 0660

