







SIQ18FP1NC2

| | |
|---|--|
| Product | Square Inductive |
| Serial | SIQ Series Square Inductive |
| Body Material | Plastic |
| Type | Flush |
| Output/Contact Type | NPN-NO |
| Sensing Distance | 5mm |
| Connection Type | 2m Cable |
| Connection / Nominal Dimension | 18 mm |
| Mounting | Flush |
| Operational Voltage | 10-30V DC |
| Insulation Voltage (Ui) | 1500 VAC |
| Impulse Withstand Voltage (Uimp) | 75V DC |
| Operating Temperature | -25°C...+70°C |
| Pollution Degree | 3 |
| Protection Degree | IP67 |
| Hysteresis | <%15 Sr (effective operating distance) |
| Number of Contact | 1 |
| Repeat Accuracy | <0,1 Sr |
| Switching Frequency | 800 Hz |
| Reverse Polarity Protection | Available |
| Short Circuit Protection | Available |
| Max. Load Current | 200 mA hiccup |
| Temperature Drift | <0,1 Sr |
| Time Delay Before Availability | ≤100 ms |
| No Load Current | < 15 mA |
| Leakage Current | ≤0,5mA |
| Min. Load Current | < 1mA |

| | |
|---|---------------------------------------|
| Voltage Drop | < 2 V |
| Ripple (Voltage) | < %10 |
| EMC | 61000-4-3 3V/m -- 61000-4-6 3 |
| Conditional Short Circuit Current | 100A |
| Usage Category - Operating Current | DC13 - 200mA |
| Sensing Face | PBT |
| Number of Cable and Cable Section | 3 x 0,25 mm ² |
| Specifications | Fast switching |
| | Resistant to friction and attrition |
| | Short circuit and overload protection |
| | Reverse polarity protection |
|     | |

