



### SKF1A-30ND

|                                              |                                                                |                 |
|----------------------------------------------|----------------------------------------------------------------|-----------------|
| <b>Product</b>                               | Level Control Float Switch                                     |                 |
| <b>Type</b>                                  | Bulb                                                           |                 |
| <b>Feature</b>                               | With Diamond Weight                                            |                 |
| <b>Cable</b>                                 | 30m                                                            |                 |
| <b>Phase Number</b>                          | 1 Phase                                                        |                 |
| <b>Current</b>                               | <b>Ie</b>                                                      | 6 A (250V AC)   |
| <b>Usage Category</b>                        | AC15                                                           |                 |
| <b>Mechanical Life</b>                       | <b>Min Qty</b>                                                 | 30000           |
| <b>Electrical Life</b>                       | <b>Min Qty</b>                                                 | 10000           |
| <b>Operating Frequency</b>                   | <b>On-Off/Hour</b>                                             | Mek.120 Elk.120 |
| <b>Insulation Voltage</b>                    | <b>Ui</b>                                                      | 660V            |
| <b>Impulse Withstand Voltage</b>             | <b>Uimp</b>                                                    | 2.75 kV         |
| <b>Dielectric Strength (Body-Contact)</b>    | 2750V AC                                                       |                 |
| <b>Dielectric Strength (Contact-Contact)</b> | 1890V AC                                                       |                 |
| <b>Isolation Resistance</b>                  | 10 MΩ Min. (500 V DC)                                          |                 |
| <b>Operating Temperature</b>                 | -15 / + 80 °C                                                  |                 |
| <b>Protection Degree</b>                     | IP68                                                           |                 |
| <b>Contact Material</b>                      | AgNi                                                           |                 |
| <b>Cable Section</b>                         | 3*1 mm Kablo                                                   |                 |
| <b>Production Time</b>                       | 1.03.2022 00:00:00                                             |                 |
| <b>Serial</b>                                | SKF1A Series                                                   |                 |
| <b>Cable Type</b>                            | Neoprene                                                       |                 |
| <b>Specifications</b>                        | Easy assembly                                                  |                 |
|                                              | Feature to adjust the requested operation interval with weight |                 |
|                                              | Different cable length options                                 |                 |
|                                              | Waterproof                                                     |                 |
| <b>Standards / Certificates</b>              | TS EN 60730-2-15                                               |                 |