


SPB30UP6PC1

Product	Photoelectric Button
Serial	SPB Series Photoelectric Button
Body Material	Plastic
Type	Diffuse Reflection Momentary
Output/Contact Type	PNP-NO
Sensing Distance	15 cm Sensing Distance
Feature	PLC Control 6 Wired
Connection Type	1m Cable
Connection / Nominal Dimension	M30
Operational Voltage	12-30 VDC
Insulation Voltage (Ui)	1500 VAC
Impulse Withstand Voltage (Uimp)	75 VDC
Operating Temperature	-25°C...+55°C
Pollution Degree	3
Protection Degree	IP67
Number of Contact	1
Reverse Polarity Protection	Available
Short Circuit Protection	Available
Max. Load Current	200 mA hiccup
Time Delay Before Availability	≤300 ms
Min. Load Current	< 1mA
Voltage Drop	< 2 V
Ripple (Voltage)	< %10
EMC	61000-4-3 3V/m -- 61000-4-6 3
Conditional Short Circuit Current	100A
Usage Category - Operating Current	DC13 - 200mA

Sensing Face	PC
Number of Cable and Cable Section	6 x 0,25 mm ²
Production Time	1.06.2023 00:00:00
Specifications	Fast switching
	Resistant to friction and attrition
	Short circuit and overload protection
	Reverse polarity protection