

**SSY11**

<b>Operational Frequency</b>		50-60 Hz
<b>Product</b>		Cylindrical Fuse holders 1P
<b>Feature</b>		10*38 mm
<b>Current</b>	<b>I<sub>e</sub></b>	32A (690 V)
<b>Usage Category</b>		AC21B
<b>Mechanical Life</b>	<b>Min Qty</b>	1700
<b>Electrical Life</b>	<b>Min Qty</b>	300
<b>Insulation Voltage</b>	<b>U<sub>i</sub></b>	690V AC
<b>Impulse Withstand Voltage</b>	<b>U<sub>imp</sub></b>	6 kV
<b>Dielectric Strength (Contact-Contact)</b>		1890V
<b>Isolation Resistance</b>		10 MΩ Min. (500 V DC)
<b>Operating Temperature</b>		-20 / +70 °C
<b>Pollution Degree</b>		3
<b>Protection Degree</b>		IP20
<b>Cable Section</b>		0,75-16 mm <sup>2</sup>
<b>Screw Torque</b>		2,5 Nm
<b>Short Circuit Breaking Capacity</b>	<b>I<sub>cs</sub></b>	100 kA
<b>Production Time</b>		PA6.6 base non-flammable body; 35 mm rail assembly
<b>Serial</b>		SSY Series
<b>Standards / Certificates</b>		TS EN 60269-1/2

