



### SSY13N

<b>Product</b>	Cylindrical Fuse holders 3P + N
<b>Serial</b>	SSY Series
<b>Feature</b>	10*38 mm
<b>Operational Frequency</b>	50-60 Hz
<b>Current (Ie)</b>	32A (690 V)
<b>Usage Category</b>	AC21B
<b>Mechanical Life (Min Qty)</b>	1700
<b>Electrical Life (Min Qty)</b>	300
<b>Insulation Voltage (Ui)</b>	690V AC
<b>Impulse Withstand Voltage (Uimp)</b>	6 kV
<b>Dielectric Strength (Contact-Contact)</b>	1890V
<b>Isolation Resistance</b>	10 MΩ Min. (500 V DC)
<b>Operating Temperature</b>	-20 / +70 °C
<b>Pollution Degree</b>	3
<b>Protection Degree</b>	IP20
<b>Cable Section</b>	0,75-16 mm <sup>2</sup>
<b>Screw Torque</b>	2,5 Nm
	100 kA
<b>Production Time</b>	1.03.2021 00:00:00
<b>Specifications</b>	V0 PA 6.6 material
	Special labelling area for code writing
	Can be mounted on DIN 35 mm mounting rail
<b>Standards / Certificates</b>	TS EN 60269-1/2

