

**TSP-0.70**

Operational Frequency		50-60 Hz
Product		Thermic Protection Switch
Feature		with Enclosure
Current	I_e	16 A
Thermic Current		0,40-0,70A
Calibration Interval		
Usage Category		AC 3
Mechanical Life	Min Qty	10000
Electrical Life	Min Qty	10000
Operating Frequency	On-Off/Hour	Mek. 360 Elk. 360
Insulation Voltage	U_i	690V AC
Impulse Withstand Voltage	U_{imp}	6 kV
Dielectric Strength (Contact-Contact)		1890V
Isolation Resistance		10 MΩ Min. (500 V DC)
Operating Temperature		-5 / +40 °C
Pollution Degree		3
Protection Degree		IP65
Cable Section		0,75-4 mm ²
Screw Torque		1,8 Nm
Production Time		Adjustable overload release 13 ranges between 0.1-25 A; Short circuit release factor set at 12xI _e ; Short circuit switching capacity minimum 6 kA / 400 V
Serial		TS Series
Specifications		Adjustable overload release 13 ranges between 0.1-25 A
		Short circuit release factor set at 12xI _e
		Short circuit switching capacity minimum 6 kA / 400 V
Standards / Certificates		TS EN 60947-4-1

CE

ERT



TSE

UK
PA