



| | | |
|--|---------------------------------|-------------------------|
| VT4025 | | |
| Product | | Rotational Limit Switch |
| Type | | 1/25 |
| Contact | | 4*CO |
| Current | Ie | 10 A (250V AC) |
| Usage Category | | AC 15 |
| Mechanical Life | Min Qty | 1000000 |
| Electrical Life | Min Qty | 100000 |
| Operating Frequency | On-Off/Hour | Mech. 120 Elec. 120 |
| Insulation Voltage | Ui | 660V |
| Impulse Withstand Voltage | Uimp | 2.5 kV |
| Dielectric Strength (Body-Contact) | | 1.890V AC |
| Dielectric Strength (Contact-Contact) | | 1.890V AC |
| Isolation Resistance | | 10 MΩ Min. (500 V DC) |
| Operating Temperature | | -15 / + 80 °C |
| Pollution Degree | | 3 |
| Protection Degree | | IP67 |
| Contact Material | | AgNi |
| Cable Section | | 1.5-2.5 mm ² |
| Screw Torque | | 1.5Nm |
| Short Circuit Breaking Capacity | Ics | 1kA |
| Production Time | | 1.11.2020 00:00:00 |
| Serial | | VT Series |
| Speed | | 4 switch |
| Cam | | 20° |
| Specifications | High impact strength | |
| | V0 and Long Life Micro Switches | |
| Standards / Certificates | TS EN 60947-5-1 | |

