



<b>VT4100</b>		
<b>Product</b>		Rotational Limit Switch
<b>Type</b>		1/100
<b>Contact</b>		4*CO
<b>Current</b>	<b>Ie</b>	10 A (250V AC)
<b>Usage Category</b>		AC 15
<b>Mechanical Life</b>	<b>Min Qty</b>	1000000
<b>Electrical Life</b>	<b>Min Qty</b>	100000
<b>Operating Frequency</b>	<b>On-Off/Hour</b>	Mech. 120 Elec. 120
<b>Insulation Voltage</b>	<b>Ui</b>	660V
<b>Impulse Withstand Voltage</b>	<b>Uimp</b>	2.5 kV
<b>Dielectric Strength (Body-Contact)</b>		1.890V AC
<b>Dielectric Strength (Contact-Contact)</b>		1.890V AC
<b>Isolation Resistance</b>		10 MΩ Min. (500 V DC)
<b>Operating Temperature</b>		-15 / + 80 °C
<b>Pollution Degree</b>		3
<b>Protection Degree</b>		IP67
<b>Contact Material</b>		AgNi
<b>Cable Section</b>		1.5-2.5 mm <sup>2</sup>
<b>Screw Torque</b>		1.5Nm
<b>Short Circuit Breaking Capacity</b>	<b>Ics</b>	1kA
<b>Serial</b>		VT Series
<b>Speed</b>		4 switch
<b>Cam</b>		20°
<b>Specifications</b>		High impact strength
		V0 and Long Life Micro Switches
<b>Standards / Certificates</b>		TS EN 60947-5-1